

TECHNICAL DATA SHEET

Name

MIURA O2 FO

Code

8038 O2 FO

Product Range

Standard

EN ISO

Weight

Size range

Mondopoint

Packaging

»TOPTREKKING

O2 FO

20347:2022 +A1:2024

620 grams
(1 shoe in size 42)

38 <> 48

11

6 pairs/carton
(same size)

TECHNICAL SPECIFICATIONS



RESISTANCE,
SAFETY



ERGONOMICS
AND COMFORT



SLIP RESISTANCE
DETERGENT



FUEL OIL
RESISTANT



SHOCK ABSORBER



ANTISTATIC



WATER RESISTANT
UPPER



OUTSOLE WITH
CLEATS

SOLE

SOLE FEATURES



THERMO GRIP® soles feature a PU foam midsole and a thermo-polyurethane outsole, designed for superior grip, even weight distribution, thermal insulation, and anti-abrasion reinforcement



PROTECTIVE ELEMENTS

UPPER

LINING

FOOTBED



Multi-layer waterproof leather designed to block liquid penetration. Maintains stability and breathability, providing reliable protection in wet conditions



Ladderproof lining offering enhanced wear resistance



Removable insole that evenly distributes weight, adapts to foot morphology, and provides antistatic, antibacterial, antifungal, and ESD protection. A cushioned heel insert further enhances comfort.

EXTRA



SAFETY TECHNICAL SPECIFICATIONS

Description	Measurement Unit	Requirement	Test Result
TOE CAP: Impact resistance	mm	≥ 14	-
TOE CAP: Compression resistance	mm	≥ 14	-
ANTI-PUNCTURE PLATE: Penetration resistance	N	≥ 1.100	-
FOOTWEAR: Antistatic properties (in wet condition)	MΩ	≥ 0,1	10,1
FOOTWEAR: Antistatic properties (in dry condition)	MΩ	≤ 1.000	410
UPPER: Water vapour permeability	mg/cm2*h	≥ 0,8	0,9
UPPER: Water vapour coefficient	mg/cm2	≥ 15	15,7
UPPER: Water penetration after 60 min	g	≤ 0,2	0
UPPER: Water absorption after 60 min	%	≤ 30	2,9
INTERNAL LINING: Water vapour permeability	mg/(cm2*h)	≥ 2,0	43,8
INTERNAL LINING: Water vapour coefficient	mg/cm2	≥ 20	353,1
OUTSOLE: Abrasion resistance	mm3	≤ 150	55
OUTSOLE: Energy absorption of seat region (E)	J	≥ 20	38
OUTSOLE: Flexural resistance	mm	≤ 4	0
OUTSOLE: Interlayer bond strength	N/mm	≥ 4	9,5
OUTSOLE: Resistance to fuel oil (FO)	%	≤ 12	2,2

ADDITIONAL FEATURES

Test	Measurement Unit	Requirement	Results
Electrical resistance for ESD footwear Requirements IEC 61340-5-1:2016	MΩ	≤ 1,00	-
Resistance to hot contact (HRO)	-	autoles shall not melt and develop any cracks when bent	-
Cold insulation of outsole complex (CI) 30min/-17°C (temperature decrease on the upper surface of the insock)	°C	≤ 10	-
Heat insulation of outsole complex (HI) 30min/150°C	°C	≤ 22	-
Water resistance (WR) (Total wetted area inside the footwear)	cm2	after 80 min.	-
Electric hazard resistance (EH) 18kV / 60 Hz (Electric flux)	MΩ	≤ 100	-

STORAGE, CARE AND MAINTENANCE

- PANDA SAFETY footwear should be stored in original packaging, storage temperature should not exceed 35°C, humidity should be less than 80% and without the influence of direct sunlight.
- Sandals, shoes and boots should be cleaned after each use; dry off the shoes, not in proximity to or in direct contact with stoves or other sources of heat.
- Carry out the periodic treatment of the uppers with suitable products containing wax, grease, silicone, etc.
- Avoid contact with aggressive chemicals and extreme temperatures.
- Verify the good state before each use.

SOLE DESIGN AND PERFORMANCE



TRACTION	STABILITY	GRIP	BRAKING	SELF-CLEANING	LADDER GRIP

ENERGY ABSORPTION COEFFICIENT IN THE HEEL AREA				
0	MINIMUM VALUE REQUIRED	20	TEST RESULT	38
				90%

INDUSTRIES

