



## MANUAL

**WELDAS PRODUCT:**  
10-2392, 10-2392GB, 10-2392LH, 10-2392/18, 10-2392MIT

This product is in compliance with the regulation (EU) 2016/425

EN12477:2001+A1:2005, Type A

Glove type: welding glove

Size: see imprint on glove

### Sizing according to EN420 : 2003 + A1 : 2009

| Hand Size Index             | 7½  | 9             | 9½  | 10½ | 11½  |
|-----------------------------|-----|---------------|-----|-----|------|
| Weldas Size Label           | S   | L             | XL  | XXL | XXXL |
| Measurement in mm           | 190 | 229           | 241 | 267 | 293  |
| Total length of glove in mm | 320 | 330 (/18=460) | 340 | 350 | 360  |



### Health information:

The pH, Chromium (VI) and PCP levels of all materials have been tested and meet CE health standards.  
Coloring: coloring is done by using natural materials

### Instruction for use:

This glove is intended to be used as a welding glove for MIG/MAG as well as electrode welding.  
There is no standardised test method at present for detecting U.V. penetration of materials for gloves but the current methods of construction of protective gloves for welders do not normally allow penetration of U.V. radiation.  
With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.  
The service life depends on the degree of wear and use intensity in the respective application areas. Temporal information is therefore not possible.  
This glove should not be worn when there is a risk of entanglement by moving parts of machines.

### Warranty:

This product is warranted against manufacturing defects.  
Because applications vary, it is the user's responsibility to identify the right product for each application.

### Washing, drying and ironing:

No washing, tumble drying and ironing is allowed.

### UV:

Within this norm there is no test method indicated on UV radiation but, normally, this will give no problem with these materials used.

### Electrical danger:


When gloves are intended for arc welding; these gloves do not provide protection against electric shock caused by defective equipment or live working, and the electrical resistance is reduced if gloves are wet, dirty or soaked with sweat, this could increase the risk.

### Materials used:

This glove is made of shoulder split cowhide.  
The lining made of cotton.  
This glove is sewn with 3 ply Dupont KEVLAR®.

### The following explains the pictograms marked on the glove:

### Mechanical risks: EN 388:2016 + A1 : 2018



3243X

| Digit | Test Resistance        | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 |
|-------|------------------------|---------|---------|---------|---------|---------|
| 1st   | Abrasion (# cycles)    | 100     | 500     | 2000    | 8000    | —       |
| 2nd   | Blade cut (index)      | 1,2     | 2,5     | 5,0     | 10,0    | 20,0    |
| 3rd   | Tear (Newton)          | 10      | 25      | 50      | 75      | —       |
| 4th   | Puncture (Newton)      | 20      | 60      | 100     | 150     | —       |
| 5th   | TDM Cut resistance (N) | A       | B       | C       | D       | E       |
|       |                        | 2       | 5       | 10      | 15      | 22      |
|       |                        |         |         |         |         | F       |
|       |                        |         |         |         |         | 30      |

### Thermal risks: EN 12477 : 2001+A1 : 2005



41324X

| Digit | Test resistance   | Digit | Test Resistance                  |
|-------|-------------------|-------|----------------------------------|
| 1st   | Burning behaviour | 5th   | Small splashes of molten metal   |
| 2nd   | Contact heat      |       |                                  |
| 3rd   | Convective heat   | 6th   | Large quantities of molten metal |
| 4th   | Radiant heat      |       |                                  |

If indication on product is "X": than the indicated position has not been tested

### EN12477 : 2001 + A1 2005: Protective gloves for welders (minimum requirements)

| Requirements                    | EN       | Type A<br>Minimum Rating | Type B<br>Minimum Rating |
|---------------------------------|----------|--------------------------|--------------------------|
| Electrical Insulation           | pr1149-2 | R≥10 <sup>6</sup> Ω      | R≥10 <sup>5</sup> Ω      |
| Abrasion Resistance             | EN388    | 2                        | 1                        |
| Blade Cut Resistance            | EN388    | 1                        | 1                        |
| Tear Resistance                 | EN388    | 2                        | 1                        |
| Puncture Resistance             | EN388    | 2                        | 1                        |
| Burning Behaviour               | EN407    | 3                        | 2                        |
| Contact Heat Resistance         | EN407    | 1                        | 1                        |
| Convective Heat Resistance      | EN407    | 2                        | 0                        |
| Small Molten Splash Resistance  | EN407    | 3                        | 2                        |
| Dexterity (pick up of rod dia.) | EN420    | 1                        | 4                        |

### Ageing:

changing of the product performance over time during use or storage  
Note 1 to entry: Ageing is caused by a combination of several factors, such as the following:  
- cleaning, maintenance, or disinfecting process;  
- exposure to visible and/or ultraviolet radiation;  
- exposure to high or low temperatures or to changing temperatures;  
- exposure to chemicals including humidity;  
Each product contains a label with a unique code for traceability of the production process.

- exposure to biological agents such as bacteria, fungi, insects, or other pests;
- exposure to mechanical action such as abrasion, flexing, pressure, and strain;
- exposure to contaminants such as dirt, oil, splashes of molten metal, etc.;
- exposure to wear and tear.

DuPont™ and KEVLAR® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.

**Storage:** Store dry and at temperatures over 5° Celcius. Do not stack higher than 5 cartons on 1 pallet

**Caution:** Weldas gloves and clothing have been tested and certified at TÜV Rheinland LGA Products GmbH Tillystraße 2, D-90431 Nürnberg, Germany (EU no. 0197).  
For more information on EN standards, testing methods, test reports, product certifications, and other products, please e-mail us at: [europa@weldas.eu](mailto:europa@weldas.eu) or visit our web site: [www.weldas.com](http://www.weldas.com)  
Declaration of conformity, test report, certificate, manual: [www.weldas-ce.com](http://www.weldas-ce.com)

### Address information Weldas:

Weldas Europe B.V. Blankenweg 18 4612 RC Bergen op Zoom The Netherlands e-mail: [europa@weldas.eu](mailto:europa@weldas.eu)