



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/2896/161/03/23/0477

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : Bultex99 Ltd
8 Karlovsko shose Str., 4000 Plovdiv
Bulgaria

Description

PPE Type : *a safety footwear*
Product reference : FAST II LOW S1
Article code : /
Construction and material of outsole : injected ; PU/PU outsole

Pictures :



CODE: 895424
NAME: FAST II LOW S1
CE EN ISO 20345:2022
S1 SR FO
SIZE: EU 42 PRD:12.2022
COLOUR: BLACK/GREY
Bultex99 Ltd
8, Karlovsko Shose Str
4000, Plovdiv Bulgaria
RD: BG2022/23188

Reference standard : EN ISO 20345:2022

Classification : I

Category : S1 SR FO

Size range : 35-50

Toecap nature : Metallic

Insert nature : N/A

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MARCH 2023 and the user instructions index 2022-12-21.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by

Date of first issue : 24 March 2023

Nadine PIPAZ

End of validity date : 24 March 2028

CE Expert Team Coordinator



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir: Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

Bultex99 Ltd

MANUFACTURER'S TECHNICAL FILE

Reference of the product: FAST II LOW S1

Article code: /

Technical file index: 01

Last update: MARCH 2023

IDENTIFICATION

Reference of the product:	FAST II LOW S1
Article Code:	/
Technical file index :	01
Last update :	MARCH 2023

Manufacturer

Bultex99 Ltd
8 Karlovsko shose Str., 4000 Plovdiv
Bulgaria
Tel : +359 32 909 700, 909 730.
Tel : +359 32 909 709

Factories

ZHEJIANG XINCAIHONG PROTECTIVE EQUIPMENT CO., LTD
NO.4908 BINHAI 3RD LANE,AIRPORT NEW ZONE,YONGXING STREET,LONGWAN DISTRICT,
WENZHOU, ZHEJIANG
CHINA
Tel : 86-577-56956788
Fax : 86-577-86100878

Zhejiang Xincaihong Footwear Co., Ltd
No. 12 Xincaihong Road, Nanpian Industrial Area, Quxi Town, Ouhai District, Wenzhou City
China
CHINA
Tel : 0577-86100878
Fax : 0577-86100882

FOOTWEAR DESCRIPTION

Footwear description

The classification of this footwear is I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear.

The design of this footwear is A : low shoe.

Visual description

General view :



Outsole view :



Reference of the mould : 9200

Range of sizes

35-50

Construction and material of outsole

injected ; PU/PU outsole

Field of use

construction, warehouse, supermarket - for mechanical risk(without anti-puncture function)

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§1.4	Manufacturer's instructions and information is available	☒	☒	Standard
			☒	Instruction for use
				Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	☒	☒	Standard
			☒	Instruction for use
				Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	☒	☒	Standard
			☒	Instruction for use
				Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§2.14	Multi-risk PPE	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	☒	☒	Standard
			☒	Instruction for use
				Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	☒	☒	Standard
			☒	Instruction for use
			☒	Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	☒	☒	Standard
				Instruction for use
				Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒	Standard
			☒	Instruction for use
			☒	Marking

FOOTWEAR CONSTITUTION

	Reference	Material	Color
UPPER	F57-1	FLYKNIT MESH	BLACK/GREY
	293	MICROFIBER(TOE PUFF)	BLACK
	007	METAL EYELET	BLACK
COLLAR	F57-1	FLYKNIT MESH	BLACK/GREY
TONGUE	LB149	SANDWICH MESH	BLACK
VAMP LINING	LB211	NON-WOVEN FABRIC LINING	WHITE
QUARTER LINING	LB149	SANDWICH MESH(TONGUE LINING; QUARTER & HEEL AREA LINING)	BLACK
INSOLE	FL104	NON WOVEN FABRIC INSOLE	BEIGE
IN SOCK	STYLE1	TERRY + EVA WITH MICRO-PERFORATED REMOVABLE IN SOCK	BLACK/GREY
OUTSOLE	9200	PU/PU DUAL DENSITY OUTSOLE	BLACK/GREY
TOE CAP	604	STEEL TOECAP	GREY
DECORATIVE ELEMENTS		WEBBING(HEEL PULL LOOP)	BLACK
		WEBBING(TONGUE NOSE)	BLACK
		TWILL FABRIC(BINDING)	BLACK

PROTECTION SCOPE

Basic requirements

This product has been designed to be a safety footwear.

The applicable basic requirements are detailed in the following standard(s):

- EN ISO 20345:2022 Safety footwear

This product is a category II PPE.

At the date of the certificate, the product is in compliance with Annex XVII of the European REACH regulation (n° 1907/2006 and revisions)

Additional requirements

The claimed additional requirements are :

- Closed seat region
- Cleated outsole
- Antistatic footwear
- Energy absorption of seat region
- Slip resistance (ceramic tile with glycerine)
- Outsole : Fuel oil resistance

MARKING - PACKAGING

Information marked on the footwear

- * Logo of the Manufacturer
- * Logo 
- * Manufacturer's name or commercial brand
- * Manufacturer's postal address
- * Manufacturer's type designation
- * Size
- * At least year and month of footwear manufacture
- * The number and year of the applicable specific standard(s)
- * The appropriate codes of marking according to the applicable requirements and additional protection and performance claimed

Marking example

CODE: 895424
 NAME: FAST II LOW S1
 EN ISO 20345:2022
 S1 SR FO
 SIZE: EU 42 PRD:12.2022
 COLOUR: BLACK/GREY
 Bultex99 Ltd
 8, Karlovsko Shose Str
 4000, Plovdiv Bulgaria
 RD: BG2022/23188

The location of the marking is : tongue lining

Method of marking on the footwear: stitching tongue lining

Packaging

1pair/color shoe box, 10pairs/CTN

References of test reports performed in order to verify the compliance with the requirements of the technical rules:

Laboratory	References	Laboratory	References
CTC	D180713248_1	CTC	D220304039_1
CTC	D181121055_1	CTC	D220405335_1
CTC	D200506225_1	CTC	D220612085_1
CTC	D200913823_1	CTC	D220816053_1
CTC	D201117401_1	CTC	D220817425_1
CTC	D210509071_1	CTC	D221021680_1
CTC	D210609922_1	CTC	D221125799_1
CTC	D210714178_1	CTC	D221126100_1
CTC	D210917199_1	CTC	D221228184_1
CTC	D211121757_1	CTC	D230303332_1
CTC	D211224332_1	Intertek	GZHT91161786

MEANS OF CONTROL

1.To control the quality of raw materials follow the methods below:

We asked our suppliers to test their upper leather for Cr VI, PH and DMFu by themselves; asked lining suppliers to check tear strength, especially abrasion resistance; and the suppliers for toecaps and insert need to test impact/compression and penetration resistance for their components...after all raw material can reach relevant requirement, we will accept them and use in mass production.

2. During development, we will take some samples to check the main physical properties, such as impact, compression, slip resistance, antistatic and so forth, in order that we can control the quality from development and will avoid some additional troubles in the following steps; if the result can meet requirement, we will process forward; otherwise we need pay more attention to development for the better shoes;

3. We control the whole procedure from cutting to package. Every step, relevant QC will check the quality, the semi-finished goods and finished shoes will be discarded if cannot reach requirement of quality. Of course we take some samples from line to test bond strength, impact ect to confirm the mass production are under control. Finally, before shipment, the QC will perform the final inspection randomly, the shoes will be delivered in case the result is acceptable.

4. When do bulk the production each batch, we shall pick up some shoes from producing site randomly to test impact, compression, antistatics, leather CR VI.... to control the quality to match the requirment of standand EN ISO 20345:2022."

PPE subject to ageing :

The design performance of this product can be affected by ageing. The peremption period is estimated at 2 years when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear...).

Declaration of conformity :

The EU declaration of conformity can be accessed on the website: www.stenso.net